

Essential Pedestrian with Three Rails

De X-Protect Essential Pedestrian Barrier met drie rails biedt extra slagvastheid en zichtbaarheid voor veilige, duidelijk afgebakende voetpaden. Ideaal voor zones met licht verkeer, verbetert deze barrière de scheiding tussen mensen en voertuigen en houdt tegelijkertijd de indeling open en efficiënt.



De Essential Pedestrian Barrier met drie rails biedt een verbeterd beschermingsniveau voor gebieden waar extra hoogte en zichtbaarheid vereist zijn. Het is ontworpen voor lichte impactzones en creëert veilige, duidelijk afgebakende looppaden met behoud van een open en efficiënte indeling.

Om de veiligheid op de locatie verder te verbeteren, kan de Floor Barrier in deze configuratie worden geïntegreerd. Deze fungeert als een solide basiselement dat het onderste deel van het systeem versterkt en extra bescherming biedt tegen risico's op grondniveau, zoals vorken van voertuigen, pallets en puin. Deze combinatie zorgt voor een doorlopende barrière die zowel de zichtbaarheid als de schokbestendigheid verbetert, terwijl het verkeer tussen de zones soepel blijft verlopen.

De installatie is snel en efficiënt, met minimale bevestigingen en zonder onnodige belasting van de vloer.

Belangrijkste kenmerken

- Snel te installeren
- Vloervriendelijk
- Gemakkelijk te vervangen

Testresultaten Impact					
Area of impact	Load	Equivalent to		90° Deflection	Force to fixings
Centre of barrier C - C as below					
1500mm	2000 J	2500kg 4.6 km/h	1500kg 5.9 km/h	334mm	4.2kN
2000mm	2250 J	2500kg 4.8 km/h	1500kg 5.9 km/h	414mm	5.1kN
Posts					
End post	1300 J	2500kg 3.7 km/h	1500kg 4.7 km/h	550mm	6.1kN
Mid post	1300 J	2500kg 3.7 km/h	1500kg 4.7 km/h	525mm	5.6kN

Modellen

Posts 3 artikelen

ARTIKELN / OMSCHRIJVING		HOOGTE (MM)	LENGTE (MM)	CC (MM)	ANDERE
	BCC0-116-00P3 Corner post	1160		2000	Compatible with the Floor Barrier
	BEE0-117-00P3 End post	1170		2000	Compatible with the Floor Barrier
	BEM0-117-00P3 Mid post	1170		2000	Compatible with the Floor Barrier

Hand rails 5 artikelen

ARTIKELN / OMSCHRIJVING		HOOGTE (MM)	LENGTE (MM)	CC (MM)	ANDERE
	RCP1-027-0050 Hand rail		270	500	
	RCP1-047-0070 Hand rail		470	700	

	RCP1-077-0100 Hand rail	770	1000
	RCP1-127-0150 Hand rail extrusion, C-C=1500mm, RAL 1018 yellow	1250	1500
	RCP1-177-0200 Hand rail extrusion	1770	2000

Gerelateerde producten

X-PROTECT

Standalone Floor Barrier




Het is ontworpen als een standalone oplossing en verbetert de bescherming van omheiningen van gebouwen en vitale infrastructuur tegen de dagelijkse risico's van vorken van voertuigen, pallets in do...

[17 artikelen](#)

X-Protect is **Safe**

- ✓ Our impact protection products undergo rigorous testing at our state-of-the-art testing facility.
- ✓ With decades of experience in industrial safety, we've designed our impact protection to perform effectively in real-world conditions.
- ✓ We know safety and can guide you to the best solutions tailored to your specific needs.



X-Protect is **Modular**

- ✓ Quickly modify barrier specifications with minimal waste.
- ✓ Perform easy and cost-effective repairs at a component level.
- ✓ Quickly build strong integrated installations with few parts.



X-Protect is **Sustainable**

- ✓ Simple end of life dis-assembly, even after an accident.
- ✓ Single material components that are easy to recycle.
- ✓ Repairable by design, damaged or worn components are easily replaced extending the barrier's life.



X-Protect components

These are the building blocks of our modular Impact Protection range.

BARRIERS & RAILS

Hand Rails



Width x Height:

68 x 72 mm | 2 11/16" x 2 27/32"

Length:

270 - 1770 mm | 10 5/8" - 69 11/16"

Impact Barriers



Width x Height:

116 x 220 mm | 4 9/16" x 8 21/32"

Length:

270 - 2770 mm | 10 5/8" - 109 1/16"

POSTS & BOLLARDS



Height:

350 - 1160 mm

13 13/16" -

45 11/16"

Width:

200 mm

7 7/8" in



Component Colours



RAL 1018




RAL 9011

X-Protect Standard Configurations

+ the highest impact energy (J) they are capable of withstanding*



* The highest force depends on the C-C. More information is available upon request.



Impact testing

This is how we calculate the energy from a vehicle impact.



Loaded weight
**3600 kg /
7930 lbs**



Loaded weight
**2700 kg /
5940 lbs**




Loaded weight
**2100 kg /
4620 lbs**

Speed	Load
6 km/h 3.7 mph	5020 J
8 km/h 5 mph	8880 J
12 km/h 7.5 mph	19960 J

Speed	Load
6 km/h 3.7 mph	3770 J
8 km/h 5 mph	6660 J
12 km/h 7.5 mph	14970 J

Speed	Load
6 km/h 3.7 mph	2930 J
8 km/h 5 mph	5180 J
12 km/h 7.5 mph	11670 J


Operating temperature



Assembly



SCAN THE CODE TO
DOWNLOAD OUR
ASSEMBLY MANUALS



1. Bollards
2. Impact
3. Impact High
4. Double Impact Low
5. Double Impact High
6. Pedestrian
7. Pedestrian + Impact
8. Pedestrian + Impact High
9. Pedestrian + Double Impact
10. Pedestrian Gate
11. Column Guard
12. Floor Barrier

The Floor Barrier can be used in combination with configurations: **3, 6, 8 & 9**